LEGEND

- Existing Fabric
- Proposed Fabric to Existing Buildings
- Proposed Fabric to New Building
- New or Adjusted Opening

EXISTING BUILDINGS - NOTES

GENERAL

All works will be carried out in accordance with current conservation best practice, where appropriate, and in accordance with the recommendations of the Conservation Plan. Any replacement using a combination of conservation and sacrificial materials will be carefully considered and specialist advice sought where appropriate.

ROOFS

Slate roofing: Slate roofing and slates with natural slate with lead/copper gutters and lead/copper flashings. Slate roofing and slates with natural slate with lead/copper gutters and lead/copper flashings. Ventilation to roof void. Repair masonry chimneys, renewing pointing of brickwork and renewal of lead/copper flashings and cleaning and repointing as required. Repair and renew cast iron rainwater goods and downpipes using traditional methods and materials. Repair and renew cast iron ventilation grilles. Repair and renew copper/zinc flashings and lead/copper flashings. Repair and renew slate roofs and slate and copper/zinc/felt flashings to the flat roofs.

New Roofs:
Slate roofing: Slate roofing and slates with natural slate with lead/copper gutters and lead/copper flashings.

FACADES

South Facade Work:
Brick wall painting, repointing and pointing in lime, providing with very lightly pointed brickwork. Repair and renew cast iron rainwater goods and downpipes using appropriate conservation cleaning techniques. Alter elevation to provide new entrance door to Hugh Lane Gallery. Remove existing door and infill with matching brickwork. Remove existing paint from stone pediments using appropriate conservation cleaning techniques. Alter elevation to provide new entrance door to Hugh Lane Gallery. Remove existing door and infill with matching brickwork. Remove existing paint from stone pediments using appropriate conservation cleaning techniques. Repair and renew cast iron rainwater goods and downpipes using traditional methods and materials. Repair and renew copper/zinc flashings and lead/copper flashings. Repair and renew copper/zinc flashings and lead/copper flashings. Remove existing paint from stone pediments using appropriate conservation cleaning techniques. Remove existing paint from stone pediments using appropriate conservation cleaning techniques. Remove existing paint from stone pediments using appropriate conservation cleaning techniques